

AD-A035 031

ARMY ELECTRONICS COMMAND FORT MONMOUTH N J
A METHOD TO OBTAIN DIFFUSE REFLECTANCE MEASUREMENTS FROM 1.0 TO--ETC(U)
NOV 76 J B GILLESPIE, J D LINDBERG
ECOM-5806

F/G 14/2

UNCLASSIFIED

NL

[OF]
AD
A035031



END

DATE
FILMED
3-77



COPY AVAILABLE TO DDC DOES NOT
PERMIT FULLY LEGIBLE PRODUCTION

AD

Reports Control Symbol
OSD-1366

ADA 035031

9

RESEARCH AND DEVELOPMENT TECHNICAL REPORT.

14

ECOM-5806

12

6

A METHOD TO OBTAIN DIFFUSE
REFLECTANCE MEASUREMENTS FROM 1.0 TO 3.0 μ m
USING A CARY 171 SPECTROPHOTOMETER.

Micrometers

16

11161102B53A

By

10

James B./Gillespie
James D./Lindberg

Atmospheric Sciences Laboratory

US Army Electronics Command
White Sands Missile Range, New Mexico 88002

12 14p.

11

November 1976

DDC
RECEIVED
JAN 31 1977
C

Approved for public release; distribution unlimited.

ECOM

UNITED STATES ARMY ELECTRONICS COMMAND - FORT MONMOUTH, NEW JERSEY 07703

2473

037620

LB

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The citation of trade names and names of manufacturers in this report is not to be construed as official Government endorsement or approval of commercial products or services referenced herein.

Disposition

Destroy this report when it is no longer needed. Do not return it to the originator.

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER ECOM-5806 ✓	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) A METHOD TO OBTAIN DIFFUSE REFLECTANCE MEASUREMENTS FROM 1.0 to 3.0 μ m USING A CARY 17I SPECTROPHOTOMETER		5. TYPE OF REPORT & PERIOD COVERED
7. AUTHOR(s) James B. Gillespie James D. Lindberg		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Atmospheric Sciences Laboratory ✓ White Sands Missile Range, New Mexico 88002		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Electronics Command Fort Monmouth, New Jersey 07703		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS DA Task No. 1L161102B53A
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE November 1976
		13. NUMBER OF PAGES 18
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Diffuse reflectance spectroscopy Integrating sphere Spectrometers		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This report describes a way to perform diffuse reflectance measurements over the 1.0 to 3.0 μ m spectral interval by using a Cary 17I Spectrophotometer equipped with inexpensive standard accessory cell-space integrating spheres. The method involves coating the cell-space spheres with a powder of pure grade quenched sulfur with carbon disulfide used as a solvent and making a minor alteration in an electronic amplifier. A spectrum of ground gypsum crystal in the 2.6 to 3.0 μ m spectral region and a spectrum of a layer of Hectorite clay in the 1.0 to		

DD FORM 1 JAN 73 1473
micrometers

EDITION OF 1 NOV 65 IS OBSOLETE

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

next
page

cont.
→

20. ABSTRACT (cont)

3.0 ^{micrometers} spectral region are presented to illustrate the applicability of the above technique for making diffuse reflectance measurements in the near infrared.

ACCESSION for	
MTIS	White Section <input checked="" type="checkbox"/>
DDC	Buff Section <input type="checkbox"/>
UNANNOUNCED	<input type="checkbox"/>
JUSTIFICATION	
BY	
DISTRIBUTION/AVAILABILITY CODES	
Dist.	Avail. and/or SPECIAL
A	

CONTENTS

	<u>Page</u>
INTRODUCTION	2
PROCEDURE	2
RESULTS AND CONCLUSIONS	4

INTRODUCTION

Optical constants of the atmospheric particulate matter are needed because of the Army's interest in the propagation of electromagnetic radiation in the visible and near infrared portion of the spectrum. Since transmission measurements do not yield acceptable techniques for determining the absorption coefficient of particulate matter suspended in the atmosphere, diffuse reflectance techniques have been developed and applied to the problem [1,2]. These techniques have been used in the 0.4 to 2.5 μ m spectral region for quantitative determinations of the absorption coefficients of clay minerals [3,4] and have also been used in the 0.3 to 1.1 μ m spectral region on atmospheric dust [5]. The absorption coefficients for the very strong water band absorption region from 2.7 to 3.0 μ m have not been determined for powdered material. This absorption region is present in the clay minerals which make up a significant portion by mass of the atmospheric dust.

The limiting factor in the useful spectral range of diffuse reflectance measurements has been the reflectance of the white standard (the sphere coating material and/or the reference material) which determines both the efficiency of the integrating sphere and the applicability of the white standard as a diluting mix for the quantitative measurements of strongly absorbing powders. Recently, a highly refined barium sulfate powder has been used in diffuse reflectance measurements. However, barium sulfate slightly absorbs water, and therefore, its reflectance is poor beyond about 2.0 μ m in the near infrared. As a diluent its absorption now becomes nontrivial and its effective spectral range of use is reduced to about 1.7 μ m [6]. As a sphere coating it is usable out to about 1.5 μ m for the small, inexpensive commercially available Cary accessory cell-space integrating spheres [7] and can be used to about 2.5 μ m in larger more efficient spheres [3,4]. Skelensky *et al.* [8] have extended the usable spectral range of the Cary accessory integrating spheres to about 2.5 μ m by coating the spheres with an alumina powder instead of barium sulfate. They used a 0.01% solution of carboxyl-methylcellulose (CMC) as a binder. However, the CMC binder contains water and therefore reduces the use of the coating - especially in the 2.5 to 3.0 μ m spectral range.

The purpose of this report is to describe a way of extending the spectral range of applicability of the inexpensive Cary accessory cell-space integrating spheres to about 3.0 μ m by using a Cary 17I spectrophotometer with slight modification to an electronic amplifier and by using a more highly reflecting, anhydrous white standard as a sphere coating.

PROCEDURE

Initially, a sphere coating of aluminum oxide particles with 0.01% CMC binder as in the work of Skelensky *et al.* was tried, but there was

insignificant signal beyond $2.5\mu\text{m}$ to operate the slit servomechanism. As an alternative to the aluminum oxide and CMC coating, powders of flowers of sulfur and a pure grade quenched sulfur which have been shown to have a high reflectance in the infrared [9] were tried. The sulfur has a lower spectral limit of $0.5\mu\text{m}$ where it begins to absorb strongly. The cell-space spheres were first cleaned and polished. Then flowers of sulfur were mixed with carbon disulfide and sprayed onto the spheres with a paint sprayer. The flowers of sulfur are about 30% μ -form sulfur, which is insoluble in carbon disulfide. A part of the sulfur went into solution and recrystallized to form a binder after it was sprayed on the sphere surfaces. Several coatings were applied at about 15-minute intervals to allow the carbon disulfide to evaporate. The final layer on the surface was very sturdy and about 3 mm thick. This coating on the spheres allowed sufficient signal to operate the slit servomechanism to $2.72\mu\text{m}$.

A sample of pure grade quenched sulfur (obtained from the Stauffer Chemical Company and referred to as Crystex) was tried in an effort to improve the above results. According to the manufacturer, the Crystex is a polymer-type sulfur with a molecular weight of about 100,000 and is about 87-93% insoluble in carbon disulfide. Its particle size is about $3\mu\text{m}$ and its index of refraction is about 1.9. Because Crystex is less soluble in CS_2 than the flowers of sulfur, it sprayed into a finer, more powdery layer - somewhat less sturdy than the flowers of sulfur; but it was adequately bound into a layer which was about 2-3 mm thick. When the spheres were coated with this substance the Cary 17I slit servomechanism operated out to a wavelength of $2.80\mu\text{m}$ and there was pen response at $3.0\mu\text{m}$. At the other end of the spectrum the spheres provided satisfactory operation down to $0.5\mu\text{m}$. However, for this particular model of the Cary 17I, the grating was blazed at $1.6\mu\text{m}$. Therefore, in the infrared region from 0.7 to $1.0\mu\text{m}$ the slit servo required a higher slit control setting and had a net result of increasing the noise level, widening the spectral bandwidth, and increasing the scan time.

To check the coating procedure several glass plates were spray coated to a thickness of about 3 mm with the flowers of sulfur and with the Crystex. First, a slightly yellowed (decomposed) CS_2 was used as the solvent. The reflectance of these first layers was measured compared to a reference sample dish full of flowers of sulfur. In the 2.1 to $2.8\mu\text{m}$ spectral region these layers had a reflectance of about 60% relative to the reference. Next, pure CS_2 was used and a reflectance of about 98-99% was obtained, thus indicating that care must be used in handling the CS_2 . It was observed during the coating procedure that the texture of the coating could be varied from fairly even to very lumpy depending on the spraying technique. This effect was tested by spraying several layers of Crystex with the texture varying from smooth to very lumpy. The smooth layers produced a reflectance of 98 to 99% while the lumpy layers produced a shadow effect which reduced the reflectance to about 85%.

In putting the final coating on the integrating spheres, the above observations were used as guidelines. Crystex was chosen as the sulfur to use because it sprayed into a smooth, even, powdery surface and was less affected by the CS_2 . Another consideration in its favor is its cohesiveness - it can be pressed into a sample dish and used in an upside down position. This is the configuration of the sample for the cell-space spheres. A pure grade CS_2 was used and a smooth layer of Crystex was sprayed to a thickness of about 3 mm onto each of the two cell-space integrating spheres.

To further extend the range of the technique, a minor electronic change was made in the sample/reference amplifier for the slit servo [10]. During this phase of the work the photometric signal was monitored with an oscilloscope. The gain of the amplifier was increased by a factor of 4 or 5. This caused a corresponding increase in the noise level which was somewhat compensated for by a very slow scan speed and higher pen period. Slit response was obtained to $3\mu\text{m}$ wavelength. The increased noise level is only necessary from 2.8 to $3.0\mu\text{m}$ since the slit gain can be reduced at wavelengths of $2.8\mu\text{m}$ and less.

RESULTS AND CONCLUSIONS

A diffuse reflectance spectrum using the equipment described above is shown in Figure 1 for the 2.6 to $3.0\mu\text{m}$ spectral interval. The sample is a gypsum crystal coarsely ground with a mortar and pestle. Gypsum was selected because it has strong absorption lines at $2.816\mu\text{m}$ and $2.938\mu\text{m}$. The ground gypsum was diluted with Crystex in a dilution of about one part gypsum to 100 parts Crystex. This dilution is necessary because the absorption in this region is so strong that the reflectance spectrum is effectively zero and no structure can be seen. Since the Crystex has no absorption in this region and has a very high reflectance (on the order of 99%), it can be mixed with the sample to act as a matrix. That the absorption lines can be clearly seen demonstrates the applicability of the technique out to $3.0\mu\text{m}$ in wavelength. The noise level in the figure is about 5 to 6% in the 2.8 to $3.0\mu\text{m}$ region and about 2 to 3% in the 2.6 to $2.8\mu\text{m}$ region. In the 3.0 to $2.8\mu\text{m}$ region the spectrum was run with a scan speed of 0.05 nm/sec , a pen period of 25, and with a spectral bandwidth of about 3.5 to 4.0 nm . From 2.0 to $2.6\mu\text{m}$ the scan speed was 0.2 nm/sec and from $2.5\mu\text{m}$ on down, it was 0.5 nm/sec . A potassium bromide pellet transmission spectrum of this same sample is shown in Figure 2 for comparison. Figure 3 shows a smoothed spectrum of a layer of Hectorite clay in the spectral region 1.0 to $2.5\mu\text{m}$. The noise level is about 1% in the 1.0 to $2.6\mu\text{m}$ region. Note the readily recognizable absorption bands in the 1.4 , 1.9 , 2.3 , and $2.7\mu\text{m}$ wavelength regions due to the O-H bonds in the structure of the Hectorite. Since this sample was not diluted, detail in the 2.6 to $3.0\mu\text{m}$ region cannot be seen easily. Note that the gypsum diffuse reflectance spectrum is

consistent with normal KBr pellet transmission spectrum in the spectral region, indicating that the instrument can satisfactorily measure diffuse reflectance spectra as desired, using the inexpensive cell-space accessory integrating spheres, modified as described in this report.




FIGURE 1. DIFFUSE REFLECTANCE SPECTRUM OF GROUND GYPSUM CRYSTAL DILUTED WITH CRYSTEX SULFUR IN THE 2.6 TO 3.0 μm SPECTRAL REGION.




FIGURE 2. POTASSIUM BROMIDE PELLET TRANSMISSION SPECTRUM OF GROUND GYPSUM CRYSTAL IN THE 2.6 TO 3.0 μm SPECTRAL REGION.




FIGURE 3. DIFFUSE REFLECTANCE SPECTRUM OF A PURE LAYER OF HECTORITE CLAY IN THE 1.0 TO 3.0 μm SPECTRAL REGION.

REFERENCES

1. Lindberg, J. D. and D. G. Snyder, "Diffuse Reflectance Spectra of Several Clay Minerals," Appl. Opt. 12, pp. 573-578 (1973).
2. Kortum, G., Reflectance Spectroscopy, Springer-Verlag, Berlin (1969).
3. Lindberg, J. D. and M. S. Smith, "Visible and Near-Infrared Absorption Coefficients of Kaolinite and Related Clays," Am. Mineral. 59, pp. 274-279 (1974).
4. Gillespie, J. B., J. D. Lindberg, and M. S. Smith, "Visible and Near-Infrared Absorption Coefficients of Montmorillonite and Related Clays," Am. Mineral. 57, pp. 485-493 (1972).
5. Lindberg, J. D. and L. S. Laude, "A Measurement of the Absorption Coefficient of Atmospheric Dust," Appl. Opt. 13, pp. 1923-1927 (1974).
6. Lindberg, J. D., "Absorption Coefficient of Atmospheric Dust and Other Strongly Absorbing Powders: An Improvement on the Method of Measurement," Appl. Opt. 14, pp 2813-2815 (1975).
7. Cary Model 1411750 and 1511000 Cell-Space Total Diffuse Reflectance Accessory Instruction Manual, Applied Physics Corporation, Monrovia, CA.
8. Skelensky, A. F., J. H. Anderson, Jr., and K. A. Wickersheim, "Method for Obtaining Improved Diffuse Reflectance Spectra in the Near Infrared," Appl. Spectros. 5, pp. 339-342 (1967).
9. Kronstein, M. and R. J. Kraushaar, "Sulfur as a Standard of Reflectance in the Infrared," J. Opt. Soc. Am. 4, pp. 458-465 (1963).
10. Varian Corporation, Sid Hedelman, private communication, October 1975.

ATMOSPHERIC SCIENCES RESEARCH PAPERS

1. Lindberg, J.D., "An Improvement to a Method for Measuring the Absorption Coefficient of Atmospheric Dust and other Strongly Absorbing Powders," ECOM-5565, July 1975.
2. Avara, Elton, P., "Mesoscale Wind Shears Derived from Thermal Winds," ECOM-5566, July 1975.
3. Gomez, Richard B. and Joseph H. Pierluissi, "Incomplete Gamma Function Approximation for King's Strong-Line Transmittance Model," ECOM-5567, July 1975.
4. Blanco, A.J. and B.F. Engebos, "Ballistic Wind Weighting Functions for Tank Projectiles," ECOM-5568, August 1975.
5. Taylor, Fredrick J., Jack Smith, and Thomas H. Pries, "Crosswind Measurements through Pattern Recognition Techniques," ECOM-5569, July 1975.
6. Walters, D.L., "Crosswind Weighting Functions for Direct-Fire Projectiles," ECOM-5570, August 1975.
7. Duncan, Louis D., "An Improved Algorithm for the Iterated Minimal Information Solution for Remote Sounding of Temperature," ECOM-5571, August 1975.
8. Robbiani, Raymond L., "Tactical Field Demonstration of Mobile Weather Radar Set AN/TPS-41 at Fort Rucker, Alabama," ECOM-5572, August 1975.
9. Miers, B., G. Blackman, D. Langer, and N. Lorimier, "Analysis of SMS/GOES Film Data," ECOM-5573, September 1975.
10. Manquero, Carlos, Louis Duncan, and Rufus Bruce, "An Indication from Satellite Measurements of Atmospheric CO₂ Variability," ECOM-5574, September 1975.
11. Petracca, Carmine and James D. Lindberg, "Installation and Operation of an Atmospheric Particulate Collector," ECOM-5575, September 1975.
12. Avara, Elton P. and George Alexander, "Empirical Investigation of Three Iterative Methods for Inverting the Radiative Transfer Equation," ECOM-5576, October 1975.
13. Alexander, George D., "A Digital Data Acquisition Interface for the SMS Direct Readout Ground Station—Concept and Preliminary Design," ECOM-5577, October 1975.
14. Cantor, Israel, "Enhancement of Point Source Thermal Radiation Under Clouds in a Nonattenuating Medium," ECOM-5578, October 1975.
15. Norton, Colburn and Glenn Hoidale, "The Diurnal Variation of Mixing Height by Month over White Sands Missile Range, NM," ECOM-5579, November 1975.
16. Avara, Elton P., "On the Spectrum Analysis of Binary Data," ECOM-5580, November 1975.
17. Taylor, Fredrick J., Thomas H. Pries, and Chao-Huan Huang, "Optimal Wind Velocity Estimation," ECOM-5581, December 1975.
18. Avara, Elton P., "Some Effects of Autocorrelated and Cross-Correlated Noise on the Analysis of Variance," ECOM-5582, December 1975.
19. Gillespie, Patti S., R.L. Armstrong, and Kenneth O. White, "The Spectral Characteristics and Atmospheric CO₂ Absorption of the Ho⁺:YLF Laser at 2.05 μ m," ECOM-5583, December 1975.
20. Novlan, David J., "An Empirical Method of Forecasting Thunderstorms for the White Sands Missile Range," ECOM-5584, February 1976.
21. Avara, Elton P., "Randomization Effects in Hypothesis Testing with Autocorrelated Noise," ECOM-5585, February 1976.
22. Watkins, Wendell R., "Improvements in Long Path Absorption Cell Measurement," ECOM-5586, March 1976.

23. Thomas, Joe, George D. Alexander, and Marvin Dubbin, "SATTEL — An Army Dedicated Meteorological Telemetry System," ECOM-5587, March 1976.
24. Kennedy, Bruce W. and Delbert Bynum, "Army User Test Program for the RDT&E-XM-75 Meteorological Rocket," ECOM-5588, April 1976.
25. Barnett, Kenneth M., "A Description of the Artillery Meteorological Comparisons at White Sands Missile Range, October 1974 — December 1974 ('PASS' — Prototype Artillery [Meteorological] Subsystem)," ECOM-5589, April 1976.
26. Miller, Walter B., "Preliminary Analysis of Fall-of-Shot From Project 'PASS'," ECOM-5590, April 1976.
27. Avara, Elton P., "Error Analysis of Minimum Information and Smith's Direct Methods for Inverting the Radiative Transfer Equation," ECOM-5591, April 1976.
28. Yee, Young P., James D. Horn, and George Alexander, "Synoptic Thermal Wind Calculations from Radiosonde Observations Over the Southwestern United States," ECOM-5592, May 1976.
29. Duncan, Louis D. and Mary Ann Seagraves, "Applications of Empirical Corrections to NOAA-4 VTPR Observations," ECOM-5593, May 1976.
30. Miers, Bruce T. and Steve Weaver, "Applications of Meteorological Satellite Data to Weather Sensitive Army Operations," ECOM-5594, May 1976.
31. Sharenow, Moses, "Redesign and Improvement of Balloon ML-566," ECOM-5595, June 1976.
32. Hansen, Frank V., "The Depth of the Surface Boundary Layer," ECOM-5596, June 1976.
33. Pinnick, R.G. and E.B. Stenmark, "Response Calculations for a Commercial Light-Scattering Aerosol Counter," ECOM-5597, July 1976.
34. Mason, J. and G.B. Hoidale, "Visibility as an Estimator of Infrared Transmittance," ECOM-5598, July 1976.
35. Bruce, Rufus E., Louis D. Duncan, and Joseph H. Pierluissi, "Experimental Study of the Relationship Between Radiosonde Temperatures and Radiometric-Area Temperatures," ECOM-5599, August 1976.
36. Duncan, Louis D., "Stratospheric Wind Shear Computed from Satellite Thermal Sounder Measurements," ECOM-5800, September 1976.
37. Taylor, F., P. Mohan, P. Joseph and T. Pries, "An All Digital Automated Wind Measurement System," ECOM-5801, September 1976.
38. Bruce, Charles, "Development of Spectrophones for CW and Pulsed Radiation Sources," ECOM-5802, September 1976.
39. Duncan, Louis D. and Mary Ann Seagraves, "Another Method for Estimating Clear Column Radiances," ECOM-5803, October 1976.
40. Blanco, Abel J. and Larry E. Traylor, "Artillery Meteorological Analysis of Project Pass," ECOM-5804, October 1976.
41. Miller, Walter and Bernard Engebos, "A Mathematical Structure for Refinement of Sound Ranging Estimates," ECOM-5805, November, 1976.
42. Gillespie, James B. and James D. Lindberg, "A Method to Obtain Diffuse Reflectance Measurements from 1.0 to 3.0 μm Using a Cary 171 Spectrophotometer," ECOM-5806, November 1976.

DISTRIBUTION LIST

Commanding Officer
Picatinny Arsenal
ATTN: SARPA-TS-S, #59
Dover, NJ 07801

Chief, Technical Services Div
DCS/Aerospace Sciences
ATTN: AWS/DNTI
Scott AFB, IL 62225

Commanding Officer
Harry Diamond Laboratory
ATTN: Library
2800 Powder Mill Road
Adelphi, MD 20783

Air Force Cambridge Rsch Labs
ATTN: LCH (A. S. Carten, Jr.)
Hanscom AFB
Bedford, MA 01731

Commander
US Army Electronics Command
ATTN: DRSEL-RD-D
Fort Monmouth, NJ 07703

Department of the Air Force
16WS/DO
Fort Monroe, VA 23651

Naval Surface Weapons Center
Code DT 21 (Ms. Greeley)
Dahlgren, VA 22448

Director
US Army Ballistic Research Lab
ATTN: DRXBR-AM
Aberdeen Proving Ground, MD 21005

Air Force Weapons Laboratory
ATTN: Technical Library (SUL)
Kirtland AFB, NM 87117

Geophysics Division
Code 3250
Pacific Missile Test Center
Point Mugu, CA 93042

Director
US Army Engr Waterways Exper Sta
ATTN: Library Branch
Vicksburg, MS 39180

National Center for Atmos Res
NCAR Library
PO Box 3000
Boulder, CO 80303

Commander
US Army Electronics Command
ATTN: DRSEL-CT-D
Fort Monmouth, NJ 07703

William Peterson
Research Association
Utah State University, UNC 48
Logan, UT 84322

Meteorologist in Charge
Kwajalein Missile Range
PO Box 67
APO
San Francisco, CA 96555

Commander
US Army Dugway Proving Ground
ATTN: MT-S
Dugway, UT 84022

Environmental Protection Agency
Meteorology Laboratory
Research Triangle Park, NC 27711

Head, Rsch and Development Div (ESA-131)
Meteorological Department
Naval Weapons Engineering Support Act
Washington, DC 20374

Commander
US Army Electronics Command
ATTN: DRCDE-R
5001 Eisenhower Avenue
Alexandria, VA 22304

Marine Corps Dev & Educ Cmd
Development Center
ATTN: Cmd, Control, & Comm Div (C³)
Quantico, VA 22134

Commander
US Army Electronics Command
ATTN: DRSEL-WL-D1
Fort Monmouth, NJ 07703

Commander
US Army Missile Command
ATTN: DRSMI-RFGA, B. W. Fowler
Redstone Arsenal, AL 35809

Dir of Dev & Engr
Defense Systems Div
ATTN: SAREA-DE-DDR
H. Tannenbaum
Edgewood Arsenal, APG, MD 21010

Mr. William A. Main
USDA Forest Service
1407 S. Harrison Road
East Lansing, MI 48823

Naval Surface Weapons Center
Technical Library and Information
Services Division
White Oak, Silver Spring, MD 20910

Dr. A. D. Belmont
Research Division
PO Box 1249
Control Data Corp
Minneapolis, MN 55440

Dir, Elec Tech and Devices Lab
US Army Electronics Command
ATTN: DRSEL-TL-D, Bldg 2700
Fort Monmouth, NJ 07703

Director
Development Center MCDEC
ATTN: Firepower Division
Quantico, VA 22134

Commander
US Army Proving Ground
ATTN: Technical Library, Bldg 2100
Yuma, AZ 85364

US Army Liaison Office
MIT-Lincoln Lab, Library A-082
PO Box 73
Lexington, MA 02173

Library-R-51-Tech Reports
Environmental Research Labs
NOAA
Boulder, CO 80302

Head, Atmospheric Research Section
National Science Foundation
1800 G. Street, NW
Washington, DC 20550

Commander
US Army Missile Command
ATTN: DRSMI-RR
Redstone Arsenal, AL 35809

Commandant
US Army Field Artillery School
ATTN: Met Division
Fort Sill, OK 73503

Meteorology Laboratory
AFCRL/LY
Hanscom AFB
Bedford, MA 01731

Commander
US Army Engineer Topographic Lab
(STINFO CENTER)
Fort Belvoir, VA 22060

Commander
US Army Missile Command
ATTN: DRSMI-RRA, Bldg 7770
Redstone Arsenal, AL 35809

Air Force Avionics Lab
ATTN: AFAL/TSR
Wright-Patterson AFB, Ohio 45433

Commander
US Army Electronics Command
ATTN: DRSEL-VL-D
Fort Monmouth, NJ 07703

Commander
USAICS
ATTN: ATSI-CTD-MS
Fort Huachuca, AZ 85613

E&R Center
Bureau of Reclamation
ATTN: Bldg 67, Code 1210
Denver, CO 80225

HQDA (DAEN-RDM/Dr. De Percin)
Forrestal Bldg
Washington, DC 20314

Commander
Air Force Weapons Laboratory
ATTN: AFWL/WE
Kirtland AFB, NM 87117

Commander
US Army Satellite Comm Agc
ATTN: DRCPM-SC-3
Fort Monmouth, NJ 07703

Commander
US Army Electronics Command
ATTN: DRSEL-MS-TI
Fort Monmouth, NJ 07703

Commander
US Army Electronics Command
ATTN: DRSEL-GG-TD
Fort Monmouth, NJ 07703

Dr. Robert Durrenberger
Dir, The Lab of Climatology
Arizona State University
Tempe, AZ 85281

Commander
Headquarters, Fort Huachuca
ATTN: Tech Ref Div
Fort Huachuca, AZ 85613

Field Artillery Consultants
1112 Becontree Drive
ATTN: COL Buntyn
Lawton, OK 73501

Commander
US Army Nuclear Agency
ATTN: ATCA-NAW
Building 12
Fort Bliss, TX 79916

Director
Atmospheric Physics & Chem Lab
Code 31, NOAA
Department of Commerce
Boulder, CO 80302

Dr. John L. Walsh
Code 5503
Navy Research Lab
Washington, DC 20375

Commander
US Army Air Defense School
ATTN: C&S Dept, MSLSCI Div
Fort Bliss, TX 79916

Director National Security Agency
ATTN: TDL (C513)
Fort George G. Meade, MD 20755

USAF EPAC/CBT (Stop 825)
ATTN: Mr. Burgmann
Scott AFB, IL 62225

Armament Dev & Test Center
ADTC (DLOSL)
Eglin AFB, Florida 32542

Commander
US Army Ballistic Rsch Labs
ATTN: DRXBR-IB
Aberdeen Proving Ground, MD 21005

Director
Naval Research Laboratory
Code 2627
Washington, DC 20375

Commander
Naval Elect Sys Cmd HQ
Code 51014
Washington, DC 20360

The Library of Congress
ATTN: Exchange & Gift Div
Washington, DC 20540
2

CO, US Army Tropic Test Center
ATTN: STETC-MO-A (Tech Lib)
APO New York 09827

Commander
Naval Electronics Lab Center
ATTN: Library
San Diego, CA 92152

Office, Asst Sec Army (R&D)
ATTN: Dep for Science & Tech
Hq, Department of the Army
Washington, DC 20310

Director
US Army Ballistic Research Lab
ATTN: DRXBR-AM, Dr. F. E. Niles
Aberdeen Proving Ground, MD 21005

Commander
Frankford Arsenal
ATTN: Library, K2400, Bldg 51-2
Philadelphia, PA 19137

Director
US Army Ballistic Research Lab
ATTN: DRXBR-XA-LB
Bldg 305
Aberdeen Proving Ground, MD 21005

Dir, US Naval Research Lab
Code 5530
Washington, DC 20375

Commander
Office of Naval Research
Code 460-M
Arlington, VA 22217

Commander
Naval Weather Service Command
Washington Navy Yard
Bldg 200, Code 304
Washington, DC 20374

Technical Processes Br
D823
Room 806, Libraries Div NOAA
8060 13th St
Silver Spring, MD 20910

The Environmental Rsch Institute of MI
ATTN: IRIA Library
PO Box 618
Ann Arbor, MI 48107

Redstone Scientific Info Center
ATTN: Chief, Documents
US Army Missile Command
Redstone Arsenal, AL 35809

Commander
Edgewood Arsenal
ATTN: SAREA-TS-L
Aberdeen Proving Ground, MD 21010

Sylvania Elec Sys Western Div
ATTN: Technical Reports Library
PO Box 205
Mountain View, CA 94040

Commander
US Army Security Agency
ATTN: IARD-OS
Arlington Hall Station
Arlington, VA 22212
2

President
US Army Field Artillery Board
Fort Sill, OK 73503

Commandant
US Army Field Artillery School
ATTN: ATSF-TA-R
Fort Sill, OK 73503

CO, USA Foreign Sci & Tech Center
ATTN: DRXST-ISI
220 7th Street, NE
Charlottesville, VA 22901

Commander, Naval Ship Sys Cmd
Technical Library, Rm 3 S-08
National Center No. 3
Washington, DC 20360

Commandant
US Army Signal School
ATTN: ATSN-CD-MS
Fort Gordon, GA 30905

Rome Air Development Center
ATTN: Documents Library
TILD (Bette Smith)
Griffiss Air Force Base, NY 13441

HQ, ESD/DRI/S-22
Hanscom AFB
MA 01731

Commander
Frankford Arsenal
ATTN: J. Helfrich PDSP 65-1
Philadelphia, PA 19137

Director
Defense Nuclear Agency
ATTN: Tech Library
Washington, DC 20305

Department of the Air Force
5WW/DOX
Langley AFB, VA 23665

Commander
US Army Missile Command
ATTN: DRSMI-RER (Mr. Haraway)
Redstone Arsenal, AL 35809

CPT Hugh Albers, Exec Sec
Interdept Committee on Atmos Sci
Fed Council for Sci & Tech
National Sci Foundation
Washington, DC 20550

US Army Research Office
ATTN: DRXRO-IP
PO Box 12211
Research Triangle Park, NC 27709

Dr. Frank D. Eaton
PO Box 3038
University Station
Laramie, Wyoming 82071

Commander
US Army Training & Doctrine Cmd
ATTN: ATCD-SC
Fort Monroe, VA 23651

Commander
US Army Arctic Test Center
ATTN: STEAC-OP-PL
APO Seattle 98733

Mil Assistant for Environmental Sciences
OAD (E & LS), 3D129
The Pentagon
Washington, DC 20301

Commander
US Army Electronics Command
ATTN: DRSEL-GS-H (Stevenson)
Fort Monmouth, NJ 07703

Commander
Eustis Directorate
US Army Air Mobility R&D Lab
ATTN: Technical Library
Fort Eustis, VA 23604

Commander
USACACDA
ATTN: ATCA-CCC-W
Fort Leavenworth, KS 66027

National Weather Service
National Meteorological Center
World Weather Bldg - 5200 Auth Rd
ATTN: Mr. Quiroz
Washington, DC 20233

Commander
US Army Test & Eval Cmd
ATTN: DRSTE-FA
Aberdeen Proving Ground, MD 21005

Commander
US Army Materiel Command
ATTN: DRCRD-SS (Mr. Andrew)
Alexandria, VA 22304

Air Force Cambridge Rsch Labs
ATTN: LKI
L. G. Hanscom Field
Bedford, MA 01730

Commander
Frankford Arsenal
ATTN: SARFA-FCD-0, Bldg 201-2
Bridge & Tarcony Sts
Philadelphia, PA 19137

Director, Systems R&D Service
Federal Aviation Administration
ATTN: ARD-54
2100 Second Street, SW
Washington, DC 20590

Inge Dirmhirn, Professor
Utah State University, UMC 48
Logan, UT 84322

USAFETAC/CB (Stop 825)
Scott AFB
IL 62225

Chief, Aerospace Environ Div
Code ES41
NASA
Marshall Space Flight Center, AL 35802

Director
USAE Waterways Experiment Station
ATTN: Library
PO Box 631
Vicksburg, MS 39180

Defense Documentation Center
ATTN: DDC-TCA
Cameron Station (BLDG 5)
Alexandria, Virginia 22314
12

Commander
US Army Electronics Command
ATTN: DRSEL-CT-S
Fort Monmouth, NJ 07703

Commander
Holloman Air Force Base
6585 TG/WE
Holloman AFB, NM 88330

Commandant
USAFAS
ATTN: ATSF-CD-MT (Mr. Farmer)
Fort Sill, OK 73503
2

Commandant
USAFAS
ATTN: ATSF-CD-C (Mr. Shelton)
Fort Sill, OK 73503
2

Commander
US Army Electronics Command
ATTN: DRSEL-CT-S (Dr. Swingle)
Fort Monmouth, NJ 07703
3